

FITTING INSTRUCTIONS

ERMAX SCREEN ADAPTABLE ON BMW R 1200 GS 2004/2012

Estimated fitting time : 30 mins

Fixing kit

- 2 black big head screws BHc Ø5x25
- 2 black big head screws BHc Ø5x15
- 2 rubber spacers Ø18x5
- 2 black blind nuts Ø5
- 4 rubber washers Ø6
- 1 mounting bracket

Fitting instructions

- Remove the 2 blind nuts located behind the butterfly adjusters on the curve of the screen. Unscrew the 2 butterfly adjusters and remove the 2 threaded fasteners in the grooves and, and the 2 steel washers from the threaded rod.



Washer to
remove

- Unscrew the 2 Torx nuts located in the pivot axle. Remove the screen.
- Remove the 2 black side cups from the original screen. ⚠ Please check the original assembly before removing the side cups : follow the fitting way right (R) and left (L).
- Fit the cups to the Ermax screen and then fit the screen to the bike.
- Fit the mounting bracket to the outer side of the cups and then replace the original butterfly adjusters, using the original threaded inserts and nuts.



Fitting bracket
assembly

- Use the 2 screws Ø5x25, the 2 rubber spacers Ø18x5, the 2 rubber washers and the 2 blind nuts (all supplied). Fit a rubber washer to each screw and then fit the mounting bracket by inserting a rubber spacer at each hole between the screen and the mounting bracket. Tighten everything up with the blind nuts.



Correct fitting

- Use the 2 BHc Ø5x15 screws, the 2 rubber washers (all supplied) and the 2 original pivot nuts. Fit a rubber washer to each screw and then affix the screen at the 2 lower pivot points, using the original nuts. Ensure that all the fixing screws are now securely tightened.

« CAUTION »

* Accessories gone up on the motorbike will not be any more considered as new and will be **neither retaken nor exchanged**.

* Ermax accessories are foreseen for **original equipments**. They will not be guaranteed if they are used in others conditions.

* Due to vehicles made tolerances, beyond our control, some Ermax products might need adjustings to fit.

* The mentioned label of motorbikes's manufacturers are indicated exclusively as a reference to Ermax accessories.

* Care to excessive clampings which may damage or break our plastic accessories and aluminium screws.

* In order to increase longevity of your chromed fixings, it is advised to polish them off with an anticorrosion product as WD40 ® after each washing or exposition at humid atmosphere (rain ...).